

(FORTS) GÄNGPRESSANDE SKRUV

 Raka spår	För ST-gängor		 Kryss-spår	För ST-gängor	
	CSK CSS	KFSK KFSS		RXK RXS	KFX KFXS
Mejseltjocklek x mejselbredd mm			(Phillips och Pozidriv/Supadriv)		
0,4x2,5	-	-	0	ST 2.2	ST 2.2
0,5x3 (0,5x4)	ST 2	ST 2.2	1	ST 2.9	ST 2.9
0,6x3,5 (0,6x4)	-	-	2	ST 3.5	ST 3.5
0,8x4 (0,8x5,5)	ST 2.9	ST 2.9		ST 4.2	ST 4.2
1,0x5,5 (1,0x6,5)	ST 3	ST 3.5		ST 4.8	ST 4.8
1,2x6,5	ST 4.2 ST 4.8	ST 4.2 ST 4.8	3	ST 5.5	ST 5.5
1,8x8	-	-		ST 6.3	ST 6.3
1,6x8	-	-	4	ST 8	ST 8
1,6x10	ST 5.5 ST 6.3	ST 5.5 ST 6.3		ST 9.5	ST 9.5
2x12 (2x13)	ST 8	ST 8			
2,5x14 (2,5x16)	ST 9.5	ST 9.5			

TRÄSKRUV

 Raka spår	För DIN-skruv			För SMS-skruv		
	TKS	TFS	TKFS	TKS	TFS	TKFS
	 DIN 96	 DIN 97	 DIN 95	 SMS -	 SMS 1573	 SMS 1574
Mejseltjocklek x mejselbredd (SMS 2830) mm	Diam. mm	Nr		Diam. mm	Nr	
0,5x3	2	2		-	-	
0,8x3,5	2.5	3		2.5	2	
	2.7	4				
0,8x4	3	5		2.8	4	
	3.5	6				
1,0x5,5	3.8	7		3.45	6	
	4	8				
	4.5	9				
1,2x6,5	-	-		-	-	
1,2x8	-	-		4.15	8	
	5	10		4.8	10	
	(5.5)	(12)		5.45	12	
				6.15	14	
1,6x8	6	14		-	-	
1,6x10	-	-		6.8	16	
2x12	(7)	(16)		7.5	18	
2,5x14	(10)	(24)		-	-	

 Kryss-spår (Phillips och Pozidriv/ Supadriv)	För DIN-skruv			För SMS-skruv		
	TKX	TFX	TKFX	TKX	TFX	TKFX
	 DIN 7996	 DIN 7997	 DIN 7995	 SMS -	 SMS -	 SMS -
Nr	Diam. mm	Nr		Diam. mm	Nr	
0	(2)	(2)		-	-	
1	2.5	5		-	-	
	3	5		2.8	4	
2	3.5	6		3.45	6	
	4	8		4.15	8	
	4.5	9		4.8	10	
	5	10		-	-	
3	(5.5)	(12)		5.45	12	
	6	14		6.15	14	
	(7)	(16)		6.8	16	
4	(8)	18		-	-	