

OLIKA SKRUVAR MED SÄNKHUVUD –
FÖR BERÄKNING AV FÖRSÄNKNINGSDIAMETERN



Metriskaskruv	Spårskruv		Kryss-skruv	
	90°  DIN 963 ISO-SS 2009	90°  DIN 964 ISO-SS 2010	90°  DIN 965 ISO-SS 7046	90°  DIN 966 ISO-SS 7047
Gänga	Huvuddiam. mm	Huvuddiam. mm	Huvuddiam. mm	Huvuddiam. mm
M 1	1.9	1.9	–	–
M 1.2	2.3	2.3	–	–
M 1.4	2.6	2.6	–	–
M 1.6	3	3	3	3
M 2	3.8	3.8	3.8	3.8
M 2.5	4.7	4.7	4.7	4.7
M 3	5.6	5.6	5.6	5.6
M 3.5	6.5	6.5	6.5	6.5
M 4	7.5	7.5	7.5	7.5
M 5	9.2	9.2	9.2	9.2
M 6	11	11	11	11
M 8	14.5	14.5	14.5	14.5
M 10	18	18	18	18
Gängpressandeskruv ST-gänga	Spårskruv		Kryss-skruv	
	80°  DIN 7972 ISO-SS 1482	80°  DIN 7973 ISO-SS 1483	80°  DIN 7982 ISO-SS 7050	80°  DIN 7983 ISO-SS 7051
Gänga	Huvuddiam. mm	Huvuddiam. mm	Huvuddiam. mm	Huvuddiam. mm
ST 2.2 (B2)	4.3	4.3	4.3	4.3
ST 2.9 (B4)	5.5	5.5	5.5	5.5
ST 3.5 (B6)	6.8	6.8	6.8	6.8
ST 3.9 (B7)	7.5	7.5	7.5	7.5
ST 4.2 (B8)	8.1	8.1	8.1	8.1
ST 4.8 (B10)	9.5	9.5	9.5	9.5
ST 5.5 (B12)	10.8	10.8	10.8	10.8
ST 6.3 (B14)	12.4	12.4	12.4	12.4
Sexkanthålskruv Metrisk			Sexkanthål (Insex)	
			90°  DIN 7991	
Gänga			Huvuddiam. mm	
M3			6	
M4			8	
M5			10	
M6			12	
M8 (8x1)			16	
M 10 (10x1.25)			20	
M 12 (12x1.25)			24	
M 14 (14x1.5)			27	
M 16 (16x1.5)			30	
M 18 (18x2)			33	
M 20 (20x2)			36	
M 22 (22x2)			36	
M 24 (24x2)			39	